

# COOLING SYSTEMS

## PORTABLE AC'S & HEAT PUMPS

### 1.5 TON AC/DEHUMIDIFIER

This versatile 115V portable air conditioning unit is suitable for various applications, including computer rooms, hospitals, schools & universities, laboratories, retail, process cooling, industrial environments, special events, and emergency short-term cooling needs.

The compact unit thermostatically controls temperature while managing humidity levels and preventing condensation & mold growth. It can be equipped with supply duct extensions, evaporator & condenser air plenums, a condensate collection tank, or a condensate pump for a wide array of applications.

#### TECHNICAL SPECS

BTU / Hr Input	16,800
Voltage	115V
Phase	1
Amps	14.5A @ 115V
Circuit Breaker Size	20A
Plug Configuration	NEMA 5-20p
Evaporator Air Flow	440 - 540 CFM
Condenser Airflow	630 - 770 CFM
Evaporator Air Outlet	(2) 5" Round (25' MAX)
Condenser Air Outlet	(1) 12" Round (60' MAX)
Filter Type	Washable Media
Operating Conditions	65 degF - 95 degF
Weight	185 lbs
Dimensions	27"L x 22"W x 47"H
Condensate Pump	Optional
Condensate Tank	Optional
Cerifications	ETL

